



Model #ECPN100399

DoorCam

Jobsite access control and visitor logging

- Automatically photograph all site access visits.
- Auto-capture images of deliveries to receiving area.
- Populate Procore Visitors, Deliveries, Manpower & Timecard.
- Lock or unlock keyless door entry systems
- Bi-directional voice communication for added security.

Live Streaming
VideoContinuous Video
RecordingWide Angle
of View2 Way Voice
CommunicationAI Detection
& AlertsProject Management
IntegrationsiOS & Android
Mobile AppFull Service
Support

TECHNICAL SPECIFICATIONS

- Live streaming video
- H.265, H.264 and Motion JPEG video compression
- Up to 30/25 fps in all resolutions
- HD resolution (1920 x 1080 pixels)
- Lens: 1.95 mm, F2.2; Minimum illumination: 0 lux with LED lit
- Horizontal field of view: 162°; Vertical field of view: 118°
- High-Definition continuous video recording with 60 days of retention (up to 1 year available)
- IP65/NEMA chromate aluminum and zinc enclosure
- Operational temperature -22° F to 140° F (-30° C to 60° C), Humidity: 10 - 100% RH
- Power over Ethernet IEEE 802.3af/802.3at Type 1, Class 3
- Power: typical 4 W, max 10.8 W
- Secure 256-bit AES encrypted onboard storage
- 2 way voice communication for additional security
- Industrial grade solid state embedded Linux System
- Designed for EarthCam Control Center Software